


Torus Vacuum Pumping System

W. Blanchard

C. Priniski, J. Winkelman, Y. Zhai, G. Labik

**NSTX NB Upgrade Peer Review
April 19, 2011**




*College W&M
 Colorado Sch Mines
 Columbia U
 CompX
 General Atomics
 INEL
 Johns Hopkins U
 LANL
 LLNL
 Lodestar
 MIT
 Nova Photonics
 New York U
 Old Dominion U
 ORNL
 PPPL
 PSI
 Princeton U
 Purdue U
 SNL
 Think Tank, Inc.
 UC Davis
 UC Irvine
 UCLA
 UCSD
 U Colorado
 U Illinois
 U Maryland
 U Rochester
 U Washington
 U Wisconsin*

*Culham Sci Ctr
 U St. Andrews
 York U
 Chubu U
 Fukui U
 Hiroshima U
 Hyogo U
 Kyoto U
 Kyushu U
 Kyushu Tokai U
 NIFS
 Niigata U
 U Tokyo
 JAEA
 Hebrew U
 Ioffe Inst
 RRC Kurchatov Inst
 TRINITY
 KBSI
 KAIST
 POSTECH
 ASIPP
 ENEA, Frascati
 CEA, Cadarache
 IPP, Jülich
 IPP, Garching
 ASCR, Czech Rep
 U Quebec*


TVPS

- TMPs
 - placed near TC floor to minimize the effects of the magnetic field
 - 2650 l/s pumping speed
- Magnetic shields:
 - ½” thick low carbon steel cylinders
 - shields extends 6” above/below TMPs
 - reduce the field to below 50 gauss
- Calculated effective pumping speed is approximately 1900 l/s





TMP Support Stand

- Support stand assembly for various loads:
 - Approx. 1200 lbs from vacuum
 - less than 50 lbs from magnetic forces
 - Approx 5700 ft-lbs torque for worst case TMP failure
- Support stand:
 - 3" square aluminum tubing bolted to 24" square SS plate
 - cross braces with electrical isolation




RGA and Gauging Overview

- Ion gauge assembly on each pumping duct
- RGA system and CM each on separate ducts
- All assemblies located between the ducts and the NB box





RGA System

- Reuse of most of the existing equipment
- Same differentially pumped configuration as exiting system on NSTX
- RGA assembly :
 - TMP and forepump
 - CB and bellows
 - interface , orifice and TMP isolation valves
 - ion gauge and CMs
 - Two RGAs for trend monitoring and after shot outgassing
- Small TMP will also be shielded from magnetic fields
- Same capabilities for measurements across a wide range of pressures



Gauging

- Two ion gauge assemblies and one CM assembly
- CM assembly :
 - CMs used for pumpdown, calibrations and GDC
 - CB/bellows assembly
 - pumpout and isolation valve
 - SS support plate
- Ion gauge assemblies :
 - miniature ion gauges
 - CB/bellows assembly
 - pumpout and isolation valve
 - low carbon steel shield cylinder
 - SS brackets and support plate welded to duct
 - Shields u-bolted to support plate
 - Separate bracket to hold and isolate ion gauge



Summary

- Overall design of TVPS and monitoring systems are complete
- Magnetic field reduced to less than 50 gauss
- Effective pumping speed ~ 1900 l/s
- RGA system configuration similar to existing system