ALZNameNa	Meeting Notes	Itom	Statua / Nataa	Data	Duo Data	Status Data
• AU 2 • AU Peter Version (Peter Version		liem	Status / Notes	Assigned	Due Dale	Status Date
- 4 decimation the Constraints, where the position of the constraints and the constraint in the constraint	▼ Ali Z	Ali Fred D. Working on OH Coil Opitmization				
In Probe your with rest and singly should be get price with rest and set of the should be		 All, Fred D - Working on OF Colling analysis. Expect to be done by end of 	Initial results show longer cooling times with .188 dia and	Jun 30, 2009		Jun 10, 2009
• Characoncols • Out of PA A D Characonco as backy list of type list data for move by house every type in parts of the PA and A dots And A dots • Characoncols • And PA A D Characonco as backy list of type list data for move by house every type in parts of the PA and A dots And A dots And A dots • Characoncols • Mark and every type in parts of the PA and A dots Mark and type in the PA And A dots And A dots • Mark and every type in parts of the PA and A dots Mark and type in the PA And A dots Mark and type in the PA And A dots And A dots • Mark and the PA A dots Mark and the PA And A dots Mark and A dots Mark and		June	400 psig. Will look at effect of taking into account the turn			
Image: Section of the Section of th	 Chrzanowski 					
Indeer by backs of transmission reaction weights reverse or regression reaction weights reverse or regression reaction weights reverse or regression reactions in the set reaction in the set result weights reverse or regression reaction weights reverse or result weights weights and the set reverse weights reverse or result weights weights and the set reverse weights reverse or result weights weights and the set reverse weights reverse or reverse reverse or reverse weights reverse or reverse reverse reverse reverse weights reverse or reverse reverse reverse reverse weights reverse reverse weights reverse reverse weights reverse rever		New PF1A, B & C dimensions are being laid out by Lew Morris for		Jun 10, 2009		Jun 10, 2009
Image: section of the section of th		review by Neumeyer, Menard, et al.				
Image: Integrate particular three decoders to ware particular structure to the structure to th		 Leak repair requisition has been issued to vendor for the R&D work. Should have samples back by the CDR. 				
Induction canapie mature base in the inference in t		 Meighan working on Keystone tests of the OH conductor to verify as 	Machining samples. Working setting up for tests. Ordering			Jun 17, 2009
Image: Interface the interface the solution by adding in the weeker is based on the solution in balance one goets and information into luce 2014 (1994) for adding weeker is an advect weeker is an advect in the solution in the solution in based one goets and information in the solution i		extruded shape	material.			
India (in the late and lat		HAN needs to run confirmation of hoop tension by adding in the vertical	Hatcher just iterating data with designer to develop the model. Han to run stress pass to compare with Titus's			May 13, 2009
IndexImage: series of the set in the set		field from Hatcher once he gets the coil dimensions from Bruce Paul	results in same area. (Looking for maximum vertical field)			
$ \frac{\operatorname{persons}}{\operatorname{persons}} \operatorname{persons} pe$		 In C. to take action) Need to develop method to seal existing leaks in Outer TF Leg cooling 	Procurement placed for the leak repair samples	-		Jun 17, 2009
• Lies protocype to use the use of the use in the 12 (Carring booting late of using a noticity in the during an outlog in the during and the during an outlog in the during and the during an outlog in the during and the during and the during an outlog in the during and the during anduring anduring and the during and the during anduring and the duri		passages				
Ormault Indication is due interm in purpties in its proference cance and whether is and its due interm is and/in planed. Interm is a subject of its in its proference cance and whether is and its due interm is and/in planed. Interm is a subject of its interm is a subject of its interm is and/in planed. Interm is a subject of its interm is a subject of its interm is a subject of its interm is and/in plane is a subject of its interm is interm is a subject of its interm is a subject of its interm is interm is a subject of its interm is a subject of its interm is interm is interm is a subject of its interm is a subject of its interm is interm is a subject of its interm is a subject of its interm is interm is a subject of its interm is interm is interm is a subject of its interm is		Use borescope to view the inside of the leak in the TF Outer leg cooling	Plan on doing this during an outage.	Oct 1, 2009	TBD	Apr 8, 2009
Number Average of the base at severe the purpose is in it's preformance once and whether it can be reading under used and quartifying basis. Trans design A weights, Aussis, A	T Denevilt	passage (during the outage).				
Image: Section in addition for 00 page head Image: Section in addition for addition addition addition for addition addi	▼ Denault	 Martin to look at where the pump is in it's performance curve and 		Jun 24, 2009		Jun 10, 2009
Image:		whether it can be modified for 600 psig head				
$ \begin{tabular}{l l l l l l l l l l l l l l l l l l l $	▼ Han					
Implane. Astrong COP : Non-solver ODP : Non-solver ODP : Provide the investment in the ring. North the the investment is investment in the ring. North the the investment is investment in the ring. North the investment is investment is investment in the ring. North the investment is investment is investment in the ring. North the investment is investment is investment in the ring. North the investment is investment is investment in the ring. North the investment is investment in the ring assembly. Undekt to set up tour of the ring assembly. Undekt to set up tour of the ring assembly. Undekt to set up tour of the ring assembly. Undekt to set up tour of the ring assembly. Undekt to set up tour of the ring assembly. Undekt to set up tour of the ring. North the investment is investment in the ring assembly. Undekt to set up tour of the ring. North the investment is investment in the ring of the ring assembly. Undekt to set up tour of the ring. North the investment is investment in the ring of the ring. North the investment is investment		OTF Structure: Han is adding radius rods and quantifying loads, Truss				
Image: Substrate and processes the margin local provide Tom with the development binding on the base as in the TF Coll. How will add in approved tom with use for base has been to provide the results of the ring society function to the ring societ		 Innlane Avisym OOP Non-avisym OOP 				
image and considered integration registering in the right object of the sense sense in the IT Cont. Have all distingeneral integration registers in the IT Cont. Have all distingeneregisters inthe IT Cont. Have all distingeneral integration regist		 Electromagnetic Thermal Current Diffusion – Will provide Tom with 				
Image: Pirit of ABD may be defining the stresses in the ring search ty out of the stresses in the FCB of Lin will all control to the stresses in the ring asserts, buck to strest to control to the stresses in the ring asserts, buck to strest to control to the stresses in the ring asserts, buck to strest to control to the FT run with cooling Image: Pirit of Piri		temp and current densities				
Image: and the set in the IP Conf. Image: A work and tangenetic bears of the machine with That and the hock for bear locations for restrains change and the top of the machine with That and the top top of the set locations for restrains change and the model of the set locations for restrains change and the model of the set locations for restrains change and the model of the set locations for restrains change and the model of the machine with That and Han Is look for bear locations for restrains change and the model of the machine and the model of the set locations for for design that and the coles. Work takes current the them the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the formation of the machine and the model of the machine and the machine and the model of the machine and the machine andef the machine and the machine andef the m		• PF 3 +/- 480 may be driving the stresses in the ring. Need to check the		Jun 10, 2009		Jun 10, 2009
Interface of the focusion of the ring assembly. Laster is as in plot of the original is another of the formation is another of the formatio		stresses in the TF Coil. Han will add tangential tension spokes to				
Amount of the set of both of best bouched both of best based of best based of best based on power supply colputs. Amount of the set of both of best both of best both of best based on power supply colputs. Image in the model Image in the		restrict the rotation of the ring assembly. Dudek to set up tour of the				
 HAN has developed a model of the TF Turn with cooling using in the model or survey with the currents that HAN is using a fixed have not your products and the fixed base and fixed have not your products and the impute of the model. Hatcher Hatcher Iberuption loads have not your posses than 1.0 seems appropriate due to the impute of the distinuting surface have not your supply supple. Near 2000 and fixed reserves than 1.0 seems appropriate due to the impute of the holds. Wordt cases current sentence have not your supply supple. Menard matcher distinuting surface in the colds. Wordt cases current insulation before distinuting surface in the surface of the structure. Near 2000 and the Structure TURN the supple supple sentence is the structure. Near 2000 and the Structure TURN the supple sentence is the structure. A more lented OH and PF operating envelope needs to be developed in the structure. A more lented OH and PF operating envelope needs to be developed in the structure. A more lented OH and PF operating envelope needs to be developed in access? What is allowable? A more lented of 14 -TURN is that a contern for the adaption access? What is allowable? A more lented of 14 -TURN is that a contern for the adaption access? What is allowable? A more lented of 14 -TURN is that a contern for the adaption access? What is allowable? A more lented of 14 -TURN is that access the adaption to a unitation of a structure in the odd in the adaption access? A more lented of 14 -TURN is that access the adaption to a unitation at a structure in the structure and the structure in the adaption of the structure. A more lented of 14 -TURN is the structure in the adaption access? A more adaption adaption adaption adaption adaption adaption adaptin the more adaption athe adaption the adaption adaption adap						
Hetcher • Deruption loads have noty et been tactored in . The application of a contraction of a		 HAN has developed a model of the TF Turn with cooling 	Need to have Neumeyer verify the currents that HAN is			Apr 29, 2009
• Discuption leads have not yet been factored in. The application of a draw the distributed wave distributed wa	▼ Hatcher		using in the model			
givamic load factor less than 1.0 seems appropriate due to the impuse or loading into a discription loading. American set of the discription loading. <td>* Hatcher</td> <td>Disruption loads have not yet been factored in. The application of a</td> <td>Results were distributed waiting for feedback and</td> <td>-</td> <td>Apr 2, 2009</td> <td>Jun 17, 2009</td>	* Hatcher	Disruption loads have not yet been factored in. The application of a	Results were distributed waiting for feedback and	-	Apr 2, 2009	Jun 17, 2009
Image: original production loading: Need for run influence coefficients for all of the coles. Worst case current Amount Image: original production loading: More influence coefficients for all of the coles. Worst case currents Amount Image: original production loading: More influence coefficients for all of the coles. Worst case currents disclated the sincture Amount Amou		dynamic load factor less than 1.0 seems appropriate due to the impulse	confirmation before distributing further			
• Meet to run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref Meta do run influence coefficients for all of the costs. Word Case unref		nature of the disruption loading.				
Menard Menard<		Need to run influence coefficients for all of the coils. Worst case current			Jun 24, 2009	Jun 17, 2009
Image: The list concept of the NSTX TF Cuber Log support system has no insulating breaks. Do we need to insulating? Mearard can calculate the impact once he gets the mark insulating breaks. Do we need to insulating? Mearard can calculate the impact once he gets the mark insulating breaks. Do we need to insulating? Mearard can calculate the impact once he gets the mark insulating breaks. Do we need to insulating? Mearard can calculate the impact once he gets the mark insulating breaks. Do we need to insulating? Mearard can calculate the impact once he gets the mark insulation concerns the full sets set of currents, displacements of the outer TF Legs are on the order of 16-17mm. Is that a concern for the mark insulation concerns to the mark insulation concerns to insulate sets are on the order of 16-17mm. Is that a concern for the mark insulation concerns to insulate sets are on the order of 16-17mm. Is that a concern for the mark insulation concerns to insulate sets? Mearard can calculate the AZ into the mark insulation concerns to insulate sets? Mearard can calculate the AZ into the mark insulation concerns to insulate sets? Mearard can calculate the AZ into the mark insulate sets? Mearard can calculate the AZ into the mark insulate sets? Mearard can calculate the AZ into the mark insulate sets? Mearard can calculate the AZ into the mark insulate sets are insulate insulate sets are insulate sets are insulate sets are insulated	▼ Menard	scenarios based on power supply outputs				
Insulating breaks. Do we need to insultate? resistance of the structure Image: Control of the design basis assumption Image: Control of the design basis assumption Arr (s, 2000)		The first concept of the NSTX TF Outer Leg support system has no	Menard can calculate the impact once he gets the			Apr 29, 2009
Vecumeyer • A more limited OH and PF operating envelope needs to be developed for the design basis assumption Mar 1.2000 Apr 15, 2009 Mar 6, 2000 • Perry •		insulating breaks. Do we need to insulate??	resistance of the structure			
Image: second system of the design basis assumption Image	▼ Neumeyer	A more limited OH and PF operating envelope needs to be developed	Made a lot of progress need one more meeting.	Mar 1, 2009	Apr 15, 2009	May 6, 2009
Perry Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? What is allowable? Image: set on the order of 16-17mm, is that a concern for the machine access? Image: set on the order of 16-17mm, is that a concern for the machine access? Image: set on the order of 16-17mm, is that a concern for the machine access? Image: set on the order of 16-17mm, is that a concern for the machine access and pull the vertical Bod. Image: set on the order of 16-17mm, is that a concern for the machine access and apply the vertical Bod. Image: set on the order of 16-17mm, is that a concern for the machine access and apply the vertical Bod. Image: set on the order of 16-17mm, is the machine access and apply the vertical Bod. Image: set on the order of 16-17mm, is the machine appropriate vertical Bod. Image: set on the order of 16-17mm, is the propriate vertical Bod. Image: set on the order of 16-17mm, is the propriate vertical Bod. Image: set on the order of 16-17mm, is the propriate vertical Bod. Image: set on the order of 16-17mm, is the propriate vertical Bod. Image: set on the propriate vertical Bod.		for the design basis assumption				
Image:	▼ Perry					
Image: A point the order of the 1, min, is that a doubter in or the machine is allowable? Image: A point the order of the 1, min, is that a doubter in or the machine is allowable? Image: A point the order of the 1, min, is that a doubter in or the machine is allowable? Image: A point is point is point is allowable? Image: A p		Han now has the latest set of currents, displacements of the outer 1F		Jun 10, 2009		Jun 10, 2009
Raki Image: statement of Work for power systems PSCAD simulation tool outsourcing The source is about 50% complete Image: statement of Work for power systems PSCAD simulation tool outsourcing Image: statement of Work for power systems PSCAD simulation tool outsourcing Image: statement of Work is about 50% complete Image: statement of Work for power systems PSCAD simulation tool outsourcing Image: statement of Work is about 50% complete Image: state		Legs are on the order of 16-17mm. Is that a concern for the machine				
• Statement of Work for power systems PSCAD simulation tool outsourcing This work is about 50% complete Image: Statement of Work for power systems PSCAD simulation tool outsourcing Jun 24, 2009 • Sri • Disruption Analysis of Vessel and Internals using 3d 360° model of VV. Simplete structures, and apply the vertical Bdot - for this he can calculate the AZ composes a vertical Bdot New will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components. If that looks 50K we will work on adding the AZ components were the AZ components. If that looks 50K we will work were the AZ components were the AZ components. If the AZ were this addition the AZ were the AZ were the additional additional section the additional section that be according to map your AZ's to the 3D work AT is the AZ were the A	▼ Raki					
outsourcing outsourcing <thoutsourcing< th=""> <thoutsourcing< th=""></thoutsourcing<></thoutsourcing<>		Statement of Work for power systems PSCAD simulation tool	This work is about 50% complete			Jun 24, 2009
• Disruption Analysis of Vessel and Internals using 3d 360° model of VX The plan is to take Sri's 3D model of the vessel, and first impose a vertical Bdot - for this he can calculate the AZ components. If that looks OK we will work on adding the passive plate structures and apply the vertical Bdot - This will be a check of the current paths and maybe a sanity check on loads if you can give us an estimate of an appropriate vertical Bdot or apply. Then we will do the proper ADS'S parametric design coding to may pour AZ'S to the 3D vessel model, and then use your tabulated loads/ currents to check the method. Image: Components if that Books OK we will work on adding the passive plate structures. And apply, Then we will do the proper ADS'S parametric design coding to may pour AZ'S to the 3D vessel model, and then use your tabulated loads/ currents to check the method. Image: Components if that Books OK we will be complete with write the AZ components if that Books OK we will be complete with write the forcing to may pour AZ'S to the 3D vessel model, and then use your tabulated loads/ currents to check the method. Image: Complete Will Books OK we will be complete with write the insulation between the OH and the force of the output the insulation between the OH and the use your tabulated loads/ currents to check the method. Image: Complete Will Books OK we will be complete with write the SK Structure St		outsourcing				
Impose a vertical Edot - for this he can calculate the AZ components. If that looks OK we will work on adding the passive plate structures. and apply the vertical Edot 1. This will be a check of the current paths and maybe a sanity check on loads if you can give us an estimate of an appropriate vertical Edot to apply. Then we will do the appropriate vertical Edot to apply. Then we will appropriate ve		 Disruption Analysis of Vessel and Internals using 3d 360° model of VV. 	The plan is to take Sri's 3D model of the vessel, and first			
Comparise in that does of we writed Bdot. This will be a check of the current paths and maybe a sanity check on loads if you can give us an estimate of an appropriate vertical Bdot to apply. Then we will do the proper ANSYS parametric design coding to may your Az's to the 3D vessel model, and then use your tabulated loads/ currents to check the method.Jun 10, 2009SRI ran the OH Hoop stress model. Stresses are high at more than 160 Mpa.May extract a few more things from the model but this work will be complete with writeup. New Hun indicates stresses that are acceptable with the insulation between the OH and Tb bundle.Jun 10, 2009SRI has started on the bolting analysis.Need to coordinate with Willard work<			impose a vertical Bdot - for this he can calculate the AZ			
will be a check of the current paths and maybe a sanity check on loads if you can give us an estimate of an appropriate vertical Bdot to apply. Then we will do the proper ANSYS parametric design coding to map your AZ's to the 3D vessel model, and then use your tabulated loads/ currents to check the method.Jun 10, 2009Image: the			passive plate structures. and apply the vertical Bdot This			
appropriate vertical Bdot to apply. Then we will do the proper ANSYS parametric design coding to map your AZ's to the 3D vessel model, and then use your tabulated loadsdy.accessed and the use your tabulated loadsdy.accessed and tabulated loadsdy.accessed and tabulated loadsdy.accessed and tabulated loadsdy.accessed and tabulated loa			will be a check of the current paths and maybe a sanity check on loads if you can give us an estimate of an			
Image: Construct of the problem in the SD vessel model, and then use your tabulated loads/ currents to check the method. Image: Construct of the SD vessel model, and then use your tabulated loads/ currents to check the method. Image: Construct of the SD vessel model, and then use your tabulated loads/ currents to check the method. Image: Construct of the SD vessel model, and then use your tabulated loads/ currents to check the method. Image: Construct of the SD vessel model, and then use your tabulated loads/ currents to check the method. Image: Construct of the SD vessel model, and then use your tabulated loads/ support tabulated of the SD vessel model, and then use your tabulated loads/ support tabulated of the SD vessel model, and then use your tabulated loads/ support tabulated of the SD vessel model, and then use your tabulated of the SD vessel model, and then use your tabulated loads/ support tabulated of the SD vessel model, and then use your tabulated loads/ the construct of the SD vessel model, and then use your tabulated of the SD vessel model, and then use your tabulated loads/ the construct of the SD vessel model, and then use your tabulated of the SD vessel model, and then use your tabulated loads/ the construct of the SD vessel model, and then use your tabulated of the SD vessel model, and the insulation between the OH and the construct of the SD vessel model, and the insulation between the OH and the support of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insulation between the OH and the tabulated of the SD vessel model, and the insul			appropriate vertical Bdot to apply. Then we will do the			
Image: Currents to check the method. Image: Currents to check the motel bings from the model but this work will be complete with writeup. New Run indicates stresses that are acceptable with the insulation between the OH and TF bundle. Image: Currents to check the method. Image: Currents to check the method. Image: Currents to check the motel bings from the model but this work will be complete with writeup. New Run indicates stresses that are acceptable with the insulation between the OH and TF bundle. Image: Current to check the method.			to the 3D vessel model, and then use your tabulated loads/			
160 Mpa. iii) be complete with writeup. New Run indicates stresses that are acceptable with the insulation between the OH and the		SBL ran the OH Hoop stress model. Stresses are high at more than	currents to check the method. May extract a few more things from the model but this work			Jun 10. 2009
Image acceptable with the insulation between the OH and TF bundle. in insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the insulation between the OH and TF bundle. Image acceptable with the envelope is suitably constrained Image acceptable with the envelope is suitably constrained Image acceptable with the envelope is suitably constrained Image acceptable with the envelope is suitably constrained Image acceptable with the envelope is suitably constrained Image acceptable with the envelope is suitably constrained		160 Mpa.	will be complete with writeup. New Run indicates stresses			-,
• SRI has started on the bolting analysis. Need to coordinate with Willard work Intersection Jun 10, 2009 • Titus			TF bundle.			
Items Items <th< td=""><td>• Titure</td><td>SRI has started on the bolting analysis.</td><td>Need to coordinate with Willard work</td><td></td><td></td><td>Jun 10, 2009</td></th<>	• Titure	SRI has started on the bolting analysis.	Need to coordinate with Willard work			Jun 10, 2009
Image: Construct of the conductor stude connection stude construct the envelope is suitably constrained Still showing high stress above stude at inner radius Image: Connection stude to be incorporated into the project plans to ensure that the envelope is suitably constrained Still showing high stress above stude at inner radius Image: Connection stude constrained Image: Connection stude connection stude constrained Image: Connection stude constrained		Global Model, Running, not merged well, corrections being made.	HM -Passive Plates & Upper and Lower VV. Han - TF Loop			
Image: Construction Image: Construction<			Geometry, Sri - Mid Plane Ports, HM/Sri - VV Support			
• Document OOP and IP loading Indext of the second sec		TF Bundle conductor stub corner analysis:	Still showing high stress above stub at inner radius			
• Willard • Tom Willard is working on the local mechanical details of the bolted connection, flag. Using .3 Tesla field from Hatcher. Jun 10, 2009 Jun 10, 2009 Jun 17, 2009 ▼ Woolley • A coil protection system needs to be incorporated into the project plans to ensure that the envelope is suitably constrained Reassigned to Woolley Jun 10, 2009 Jun 30, 2009 Jun 10, 2009		Document OOP and IP loading				
Image: Connection, flag. Using .3 Tesla field from Hatcher. Image: Connection, flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field from Hatcher. Image: Connection flag. Using .3 Tesla field flag. U	 vvillard 	Tom Willard is working on the local mechanical details of the bolted		Jun 10, 2009		Jun 17, 2009
 ✓ Woolley A coil protection system needs to be incorporated into the project plans Reassigned to Woolley Jun 10, 2009 Jun 30, 2009 Jun 30, 2009 Jun 30, 2009 Jun 10, 2009 Jun 30, 2009 Jun 10, 2009 		connection, flag. Using .3 Tesla field from Hatcher.				
 A conprotection system needs to be incorporated into the project plans Reassigned to Woolley Jun 10, 2009 Jun 30, 2009 Jun 30, 2009 Jun 10, 2009 	▼ Woolley		Dependent Master	him 40, 0000	him 00, 0000	
		to ensure that the envelope is suitably constrained	I TEASSIGNED TO WOULDY	JUIT IV, 2009	Jun 30, 2009	JUN 10, 2009